



System Specification	Phaser 3330
<b>One-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 42 ppm Up to 40 ppm Up to 34 ppm
<b>Two-Sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 21 ppm Up to 20 ppm Up to 17 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 80,000 pages / month
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 6,000 pages
Processor	1 GHz
Memory	512 MB
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi
Paper Handling	
Bypass Tray	
Capacity <sup>3</sup>	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies
Tray 1	
Capacity <sup>3</sup>	250 sheets
Sizes	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm
Weights	16 lb. bond to 43 lb. bond / 60 to 163 gsm
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled
Additional Tray	
Capacity <sup>3</sup>	550 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
Weights	16 lb. to 43 lb. bond / 60 to 163 gsm
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled

Total Capacity	
Device Standard Capacity <sup>3</sup>	300 sheets
Device Total Capacity <sup>3</sup>	850 sheets
Paper Output	
Output Capacity <sup>3</sup>	150 sheets
Automatic 2-Sided	Standard
Device Specification	
Electrical Requirements	
North America	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A
Power Consumption	
Operation <sup>4</sup>	Maximum 700 watts
Standby Mode <sup>4</sup>	Maximum 50 watts
Power Off Mode <sup>4</sup>	Maximum 0.1 watts
Sleep Mode <sup>4</sup>	Maximum 3.5 watts
Warm-up (from Sleep Mode)	As fast as 35 seconds
Operating Environment	
Required Temperature Range Storage Operating	32°F to 104°F / 0°C to 40°C 50°F to 90°F / 10°C to 32°C
Required Reletive Humidity	20% to 80%
Sound Power Levels Operating Standby	54 dB(A) or less 26 dB(A) or less
Sound Pressure Levels Operating Standby	54 dB(A) or less 26 dB(A) or less
Dimensions and Weight (unpackaged)	
Phaser 3330	Width: 14.4 in. / 366 mm Depth: 14.4 in. / 366 mm Height: 11.4 in. / 289.6 mm Weight: 23.37 lb. / 10.6 kg
550-sheet Paper Tray	Width: 14.4 in. / 366 mm  Depth: 17.9 in. / 454 mm  Height: 5.7 in. / 146 mm  Weight: 11.82 lb. / 5.36 kg
Dimensions and Weight (packaged)	
Phaser 3330	Width: 17.7 in. / 449.6 mm Depth: 17.7 in. / 449.6 mm Height: 15.9 in. / 403.9 mm Weight: 28.31 lb. / 12.84 kg
550-sheet Paper Tray	Width: 22.2 in. / 563 mm  Depth: 19.6 in. / 497 mm  Height: 11.2 in. / 285 mm  Weight: 16.8 lb. / 7.62 kg

System Certification/Regulatory Compliance	
System Certification/Regulatory Compliance  Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print™ 2.0 Certification Mopria® certified Wi-Fi Alliance Certified Biue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications and to warm veroe con/OfficeCertifications.
Print	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.
First-Page-Out Time	As fast as 6.5 seconds <sup>5</sup>
Resolution	Up to 1200 x 1200 dpi image quality
Page Description Languages	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG
Maximum Print Area	4 mm from all edges
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL
Operating Systems	Microsoft® Windows® Vista and later Mac OS™ 10.8.x and later Various Linux® and Unix distributions
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Bonjour® / Airprint®  IPv6  Secure FTP  Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font
Mobile Solutions and Mobile Device Apps	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.

Mobile Solutions and Mobile Device Apps			
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print <sup>™</sup>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook $^{^{\mathrm{M}}}$ notebook computers and any other web-connected device. $^{^{6}}$		
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing stapling and secure code release. A free download is available from the Google Play™ store.		
Security			
Security Features	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 IPsec WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise		
WiFi Security			
	Authentication Method  Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise WPA Enterprise Authentication Method options:  • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TTLS PAP • EAP-TTLS CHAP	Encryption  WEP 64 / 128-bit ASCII / HEX  TKIP  AES  TKIP  AES	
Device Management			
Xerox® CentreWare® Web			
Device Status	Web server embedded  • Tray status/contents  • Consumables status		
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.		
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Internet Services – Integrated Device N	Neb Page		
	A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system  Works with any SNMP-managed printer from any manufacturer  Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.		
Xerox® Standard Accounting (Standard)			
Tracking	Print usage		
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		

Remote Print Services		
Xerox® MeterAssistant® Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	<ul> <li>Phaser 3330 Printer</li> <li>Standard Capacity Print cartridge: 2,600 pages<sup>7</sup></li> <li>Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> </ul>	
Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>7</sup>	106R03623
High Capacity Print Cartridges	8,500 standard pages <sup>7</sup>	106R03621
Drum Cartridge	30,000 standard pages <sup>8</sup>	101R00555
Accessories		
	097N02254	
550-sheet Paper Tray	097N02254	
550-sheet Paper Tray  Near Field Communication (NFC) Enablement Kit	097N02254 097N02255	

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Expected regular monthly throughput.

Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Printing from USB.

Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).

Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.



