Xerox[®] Integrated Server for the B9100 Series Copier/Printer

Next-level monochrome productivity.

The Xerox® B9100 Series
Copier/Printer combines
the walk-up simplicity of an
office or work group copier/
printer with the wider
capabilities of a light
production press. Its
integrated server combines
powerful performance with
push-button-simple
usability.



Extend your capabilities with apps from the Xerox App Gallery.

- Tailor your device to work the way you do with an ever-evolving selection of innovative apps available on the Xerox App Gallery.
- Increase your opportunities with an expansive media selection – including Extra Long Sheet (XLS) for creative banner printing – and inline finishing capabilities ranging from stapling and hole-punching to folding for presentations, brochures, reports and newsletters.
- Use Xerox® Standard Accounting Feature and internal auditing to track device usage, set limits and control costs.

- Customise your print driver settings to save on specific applications.
- Maximise your productivity by performing scan, print, copy, fax* and file routing operations simultaneously.
- Easily share files or introduce electronic archiving with powerful scan capabilities.
 Text-searchable files make retrieval simple. And compression technology reduces network load for faster transmission.
- Automate document routing to predefined locations such as email addresses with job flow sheets.

- Enjoy automatic installation, troubleshooting, feature set-up and upgrades with the Xerox® Embedded Web Server.
- Replenish supplies automatically –
 Xerox® Automated Meter Readings
 (AMR) collects and submits readings,
 and Xerox® Automatic Supplies
 Replenishment (ASR) orders ink
 whenever supplies run low.
- Securely print from any email-enabled device with Xerox® @PrintByXerox App.
 No software or app to download. No IT intervention. Just send an email and print from the device.



Xerox® Integrated Server

HARDWARE SPECIFICATIONS

- Hard Drive: 320 GB Hard Disk Drive
- Processor: 1.6 GHz Dual-core
- Memory: 4 GB RAM
- OS Platform: Linux
- 10.4-inch colour touchscreen flat panel display
- 10/100/1000 MB/s standard

PRINT FEATURES

- Automatic two-sided
- Secure print
- Delay print
- Sample set
- Booklet creation
- Cover selection
- Paper selection by attribute
- N-up
- Watermarks and secure watermarks**
- Banner sheets
- Output tray selection
- Standard USB
- Mobile/Smartphone Printing

STANDARD APP CAPABILITIES

- Xerox® App Gallery App
- Xerox® @PrintbyXerox App

FAX'

- Optional Walkup PSTN fax (one-line and two-line options) with Internet fax
- Fax over IP (T.38) Kit
- Network Server Fax Enablement Kit features:
 - Fax
 - Fax Forward
 - Two-sided Send and Receive
 - Fax up to 11 x 17 in./A3

ACCOUNTING

- Xerox[®] Standard Accounting (copy, print, fax, scan)
- Network Accounting Enablement

CLIENT ENVIRONMENTS SUPPORTED

Windows

- Windows 7 SP1 (Service Pack 1), 64-bit and 32-bit
- Windows 8, 64-bit and 32-bit
- Windows 8.1 Update 1, 64-bit and 32-bit
- Windows 10, 64-bit and 32-bit
- Windows Server 2008 SP2, 64-bit and 32-bit

- Windows Server 2008 R2 SP1, 64-bit
- Windows Server 2012, 64-bit
- Windows Server 2012 R2. 64-bit
- Windows Server 2016, 64-bit
- Windows Server 2019, 64-bit

Mac OS

- Mac 10.13
- Mac 10.14
- Mac 10.15

Unix and Linux

- Red Hat Enterprise Linux 7.6 x64
- Red Hat Enterprise Linux 8 x64
- Fedora Core 29 x32
- Fedora Core 29 x64
- Fedora Core 30 x32
- Fedora Core 30 x64
- Ubuntu 18.04 x32
- Ubuntu 18.04 x64
- Ubuntu 19.04 x64
- Ubuntu 19.10 x64
- OpenSuse 15.1 x64
- Solaris 11.4 x86
- Solaris SPARC 11.4
- Power PC AIX 7.2
- Itanium HP-UX 11i v3 Update 18

Citrix

- Citrix Virtual Apps and Desktops 7 1909
- Citrix XenApp 7.15
- Citrix XenDesktop 7.15

Novell

- Open Enterprise Server 2018 SP1
- WHOL Certification

PDLs AND DATA FORMATS

- PDF, XPS®, PCL® 6, HP-GL2 (direct submission), TIFF, JPEG
- Adobe® PostScript® 3™

SCAN AND COPY

A robust set of scan/copy functions plus:

- Thumbnail Preview
- Scan to: Home, Desktop WIA, Desktop TWAIN, Mailbox, FTP, sFTP (via EIP), USB Storage Device, Remote Printer, Fax Server, SMB, Network Scanning
- Scan to: Multiple Destinations
- Scan via: SMB, HTTP, HTTPS
- High compression or quality file size settings**
- Searchable PDF**

SECURITY

- Access Controls
- AES 256-bit Encryption
- Audit Log
- Certificate Path Validation
- Certificate Revocation List (CRL)/ Status Protocol (OCSP)
- Common Criteria Certified
- Detection of External Program Falsification (XCP Plug-in)
- Domain Filtering
- FIPS 140-2
- Firmware Verification
- Immediate Disk Overwrite
- IP Address Filterina
- IPsec
- Network Authentication
- Self-Signed Certificates
- Role-Based Permissions
- Secure Print
- Security Certificate Management
- SIPRNet
- Smart Card Enablement (CAC/PIV/.NET)
- SNMPv3
- Status Protocol (OCSP)
- TLS/SSL

OTHER OPTIONS

- USB Direct Print, Media Card Reader, Common Access Card Enablement Kit
- Xerox Extensible Interface Platform® Enabled, Foreign Device Interface

ELECTRICAL REQUIREMENTS

- Printer: 110-127 VAC, 50/60 Hz
- Options: 100-240 VAC. 50/60 Hz
- Optional Feeding/Finishing
- Each module requires 100-240 VAC, 50/60 Hz power

PRINTER DIMENSIONS

Base Unit w/ Offset Catch Tray:

- Height: 54.8 in./1,391.5 mm
- Width: 62 in./1,574 mmDepth: 31.6 in./803.5 mm

For more information on the Xerox® Integrated Server, please contact your Xerox representative, call **1-800-ASK-XEROX** or visit us online at **xerox.com**.

