# Xerox<sup>®</sup> Phaser<sup>®</sup> 6510 Colour Printer





| System Specification   | Phaser 6510N  | Phaser 6510DN   | Phaser 6510DNI  |  |
|--|---|---|---|--|
| One-Sided Speed<br>8.5 x 11 in.<br>8.5 x 14 in. / 216 x 356 mm<br>A4 / 210 x 297 mm        | Up to 30 ppm Colour and Black and White<br>Up to 24 ppm Colour and Black and White<br>Up to 28 ppm Colour and Black and White                                   |   |   |  |
| <b>Two-Sided Speed</b><br>8.5 x 11 in.<br>8.5 x 14 in. / 216 x 356 mm<br>A4 / 210 x 297 mm | NA<br>NA<br>NA  | Up to 18 ppm Colour and Black and White<br>Up to 17 ppm Colour and Black and White<br>Up to 19 ppm Colour and Black and White |   |  |
| Monthly Duty Cycle <sup>1</sup>  | Up to 50,000 pages / month  |   |   |  |
| Recommended Average Monthly Print<br>Volume <sup>2</sup>                                   | Up to 3,000 pages   |   |   |  |
| Processor  | 733 MHz   |   |   |  |
| Memory   | 1 GB  |   |   |  |
| Connectivity   | 10/100/1000Base-T Ethernet<br>USB 3.0   |   | 10/100/1000Base-T Ethernet<br>USB 3.0<br>Wi-Fi 802.11n<br>Wi-Fi Direct® |  |
| Paper Handling   | Phaser 6510N  | Phaser 6510DN   | Phaser 6510DNI  |  |
| Bypass Tray  |   |   |   |  |
| Capacity <sup>3</sup>  | 50 sheets   | 50 sheets   |   |  |
| Sizes  | Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm   |   |   |  |
| Weights  | 16 lb. bond to 58 lb. cover / 60 to 220 gsm   |   |   |  |
| Media Types  | Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled |   |   |  |
| Tray 1   |   |   |   |  |
| Capacity <sup>3</sup>  | 250 sheets  |   |   |  |
| Sizes  | Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 1   | Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm  |   |  |
| Weights  | 16 lb. bond to 65 lb. cover / 60 to 176 gsm   |   |   |  |
| Media Types  | Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled |   |   |  |
| Optional Tray 2  |   |   |   |  |
| Capacity <sup>3</sup>  | 550 sheets  |   |   |  |
| <u> </u>   | 1   |   |   |  |

| Optional Tray 2                                      |   |                            |                |  |
|--|---|----------------------------|----------------|--|
| Sizes  | Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x  | 191 mm to 216 x 356 mm     |                |  |
| Weights  |   | 191 HIII W 210 A 330 HIIII |                |  |
| Media Types  | 16 lb. bond to 65 lb. cover / 60 to 176 gsm  Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled |                            |                |  |
| Total Capacity                                       |   |                            |                |  |
| Device Standard Capacity <sup>3</sup>                | 300 sheets  |                            |                |  |
| Device Total Capacity <sup>3</sup>                   | 850 sheets  |                            |                |  |
| Paper Output   |   |                            |                |  |
| Output Capacity <sup>3</sup>                         | 150 sheets  |                            |                |  |
| Automatic 2-Sided                                    | NA  | Standard                   |                |  |
| Device Specification                                 | Phaser 6510N  | Phaser 6510DN              | Phaser 6510DNI |  |
| Electrical Requirements                              |   |                            |                |  |
| North America  | Voltage: 120 VAC +/- 10 %<br>Frequency: 60 Hz +/- 3 Hz, 12A   |                            |                |  |
| Europe   | Voltage: 220-240 VAC +/- 10%<br>Frequency: 50 Hz +/- 3 Hz, 6A   |                            |                |  |
| Power Consumption                                    |   |                            |                |  |
| Operation <sup>4</sup>                               | 120V: Maximum 380 watts<br>220V: Maximum 350 watts  |                            |                |  |
| Standby Mode <sup>4</sup>                            | 120V: Maximum 41 watts<br>220V: Maximum 44 watts  |                            |                |  |
| Power Off Mode <sup>4</sup>                          | 120V: Maximum 0.2 watts<br>220V: Maximum 0.3 watts  |                            |                |  |
| Sleep Mode <sup>4</sup>                              | 120V: Maximum 0.9 watts<br>220V: Maximum 1.0 watts  |                            |                |  |
| Warm-up (from Sleep Mode)                            | As fast as 26 seconds   |                            |                |  |
| Operating Environment                                |   |                            |                |  |
| Required Temperature Range<br>Storage<br>Operating   | -4°F to 104°F / -20°C to 40°C<br>41°F to 90°F / 5°C to 32°C   |                            |                |  |
| Required Reletive Humidity                           | 15% to 85%  |                            |                |  |
| Sound Power Levels<br>Operating<br>Standby           | 6.76 B or less<br>4.00 B or less  |                            |                |  |
| <b>Sound Pressure Levels</b><br>Operating<br>Standby | 51.9 dB(A) or less<br>24.9 dB(A) or less  |                            |                |  |
| Dimensions and Weight (unpackaged)                   |   |                            |                |  |
| Phaser 6510N, and DN                                 | Width: 16.5 in. / 420 mm<br>Depth: 19 in. / 483 mm<br>Height: 13.7 in. / 347 mm<br>Weight: 52.5 lb. / 23.8 kg   |                            |                |  |
| Phaser 6510 DNI                                      | Width: 16.5 in. / 420 mm<br>Depth: 19.6 in. / 499 mm<br>Height: 13.7 in. / 347 mm<br>Weight: 52.5 lb. / 23.8 kg   |                            |                |  |

| Dimensions and Weight (unpackaged)                |   |  |
|---|---|--|
| 550-sheet Paper Tray                              | Width: 16.5 in. / 420 mm  |  |
|   | Depth: 18.3 in. / 465 mm  |  |
|   | Height: 5.9 in. / 150 mm  |  |
|   | Weight: 14.8 lb. / 6.7 kg   |  |
| Dimensions and Weight (packaged)                  |   |  |
| haser 6510N, DN, and DNI Width: 14.3 in. / 634 mm |   |  |
|   | Depth: 22.8 in. / 580 mm  |  |
|   | Height: 19.9 in. / 505 mm   |  |
|   | Weight: 64.4 lb. / 29.2 kg  |  |
| 550-sheet Paper Tray                              | Width: 21.1 in. / 535 mm  |  |
|   | Depth: 23 in. / 584 mm  |  |
|   | Height: 9.8 in. / 248 mm  |  |
|   | Weight: 18.7 lb. / 8.5 kg   |  |
| System Certification/Regulatory Complian          | ice   |  |
| Certifications                                    | FCC Part 15 Class A   |  |
|   | FCC Part 68   |  |
|   | CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition   |  |
|   | NOM   |  |
|   | GS Mark   |  |
|   | EAC<br>Citrix <sup>™</sup> Certified  |  |
|   | Citrix Certified Cerner (undergoing evaluation)   |  |
|   | Apple® AirPrint® certification  |  |
|   | Google Cloud Print <sup>™</sup> Certification   |  |
|   | Mopria® certified   |  |
|   | Wi-Fi Alliance Certified  |  |
|   | Blue Angel  |  |
|   | MEDITECH ENERGY STAR®   |  |
|   | ECOLOGO®  |  |
|   | EPEAT (United States)   |  |
|   | To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.  |  |
| Print   | Phaser 6510N Phaser 6510DN Phaser 6510DNI   |  |
| First-Page-Out Time                               | As fast as 12 seconds Colour and Black and White  |  |
| Resolution  | Up to 1200 x 2400 dpi   |  |
| Page Description Languages                        | Adobe® PostScript® 3™   |  |
|   | PCL® 5e, 6  |  |
|   | PDF<br>TIFF   |  |
| Maximum Print Area                                | 4 mm from all edges   |  |
| Maximum Fillic Area                               | 4 mm nom dit edges  |  |
| D. C. I. F I                                      | D. Cl.  |  |
| Print Features                                    | Banner Sheets   |  |
| Print Features                                    | Booklet Print   |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode   |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page   |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays   |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation  |  |
| Print Features                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print  |  |
| Print Features  Print from USB                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Secure Print  |  |
|   | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port  |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS   |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012  |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher  |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher Citrix®  |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher Citrix® Redhat® Enterprise                                 |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher Citrix® Redhat® Enterprise Linux®                          |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5              |  |
| Print from USB                                    | Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.9 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 |  |

| Print  | Phaser 6510N  | Phaser 6510DN  | Phaser 6510DNI   |
|--|---|--|--|
| Network Protocols  | TCP/IP: HTTP/HTTPS, IPP, LPR/L  | DP, Raw Socket Printing/Port 9100, IPv4/IPv6, WS   | 5D   |
|  | SMB<br>SMTP, Secure SMTP<br>LDAP, Secure LDAP<br>Bonjour® / Airprint®<br>FTP  | of man society many of the state of the stat |  |
|  | Most protocols not in use can be  | e disabled   |  |
| Administrative Protocols   | DHCP, SNMP v2/3, WINS, DHCF   | Autonet, TLS, SNTP, MDNS   |  |
| Font Capability  | 136 PostScript fonts<br>88 PCL fonts  |  |  |
| Mobile Solutions and Mobile Device Apps  |   |  |  |
| Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>  | Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.                         |  |  |
| Xerox <sup>®</sup> Global Print Driver <sup>®</sup>  | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.  |  |  |
| Apple <sup>®</sup> AirPrint <sup>®</sup>   | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.  |  |  |
| Google Cloud Print <sup>™</sup>  | Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, $Chromebook^{M}$ notebook computers and any other web-connected device.  |  |  |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)                               | The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. |  |  |
| Xerox® Wireless Print Solutions Adapter (Optional)   |   | ns Adapter seamlessly connects your Xerox <sup>®</sup> printer<br>more information, visit <mark>www.xerox.com/WPSA</mark>  | or MFP to modern mobile and desktop workflows, regardless  |
| Security   | Phaser 6510N  | Phaser 6510DN  | Phaser 6510DNI   |
| Security Features  | Secure HTTPS (TLS) IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL)   |  |  |
| Device Management  |   |  |  |
| Xerox® CentreWare® Web   |   |  |  |
|  | whether running Windows or  Works with any SNMP-manag   | UNIX or any other operating system<br>jed printer from any manufacturer  | rowser-based device management from any workstation,<br>shooting, and device upgrades, as well as basic accounting |
| ${\sf Xerox}^{\circ} \: {\sf Embedded} \: {\sf Web} \: {\sf Server} \: {\sf -Integrated} \: {\sf D}$ | evice Web Page  |  |  |
| Device Status  | Web server embedded • Tray status/contents • Consumables status   |  |  |
| Print Queue Viewing  | Complete job print queue management—hold, release, promote and delete   |  |  |
| Job Submission   | Print-ready files (PS, PCL®, PDF, XPS, JPEG) Output feature selection   |  |  |
| Device Administration  | Allows simple, remote installation  | on setting of configuration options and managen  | nent of the device.  |
| Browsers   | Microsoft® Internet Explorer 11<br>Microsoft Edge™ 38<br>Mozilla™ Firefox® 48<br>Apple® Safari® 9.1<br>Google Chrome™ 52<br>Opera™ 39   |  |  |
| Remote Print Services  |   |  |  |
| Xerox® MeterAssistant® Service   |   | ting and submitting meter reads for tracking and l<br>it and ensures that meter reads are submitted to   | billing of Xerox® device usage. Eliminates the need for time-<br>Xerox on time.                                    |
| Xerox <sup>®</sup> SuppliesAssistant <sup>®</sup> Service  | Automatically orders supplies fo  | or Xerox® output devices based on actual usage, eli  | minating the need to manually manage supplies inventory.   |
| Maintenance Assistant  |   | esolve potential issues and receive assistance and or problems to be solved faster with increased upt  | d automate the troubleshooting/repair process. Diagnostic time.  |

| What's In The Box                    |   |  |  |
|--------------------------------------|---|--|--|
|                                      | <ul> <li>Phaser 6510 Colour Printer</li> <li>Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity<sup>5</sup>; Black: 1,500 print capacity<sup>5</sup></li> <li>Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Driv and Warranty Statement)</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> </ul> |  |  |
| Supplies and Accessories             | Quantity  | Part Number                                      |  |
| Supplies                             |   |  |  |
| Extra-High Capacity Print Cartridges | Cyan: 4,300 standard pages <sup>5</sup><br>Magenta: 4,300 standard pages <sup>5</sup><br>Yellow: 4,300 standard pages <sup>5</sup>  | 106R03693<br>106R03694<br>106R03695              |  |
| High Capacity Print Cartridges       | Black: 5,500 standard pages <sup>5</sup> Cyan: 2,400 standard pages <sup>5</sup> Magenta: 2,400 standard pages <sup>5</sup> Yellow: 2,400 standard pages <sup>5</sup>   | 106R03488<br>106R03485<br>106R03486<br>106R03487 |  |
| Standard Capacity Print Cartridges   | Black: 2,500 standard pages <sup>5</sup> Cyan: 1,000 standard pages <sup>5</sup> Magenta: 1,000 standard pages <sup>5</sup> Yellow: 1,000 standard pages <sup>5</sup>   | 106R03484<br>106R03481<br>106R03482<br>106R03483 |  |
| Drum Cartridge                       | Black: 48,000 pages <sup>6</sup><br>Cyan: 48,000 pages <sup>6</sup><br>Magenta: 48,000 pages <sup>6</sup><br>Yellow: 48,000 pages <sup>6</sup>  | 108R01420<br>108R01417<br>108R01418<br>108R01419 |  |
| Waste Cartridge                      | 30,000 pages <sup>6</sup>   | 108R01416  |  |
| Accessories                          |   |  |  |
| 550-sheet Paper Tray                 |   | 097504765  |  |
| Wireless Network Adapter             |   | 497K16750  |  |

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.



Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit <a href="https://www.xerox.com/about-xerox/recycling">www.xerox.com/about-xerox/recycling</a>.



For more information, visit us at www.xerox.com/office