



System Specification	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
One-Sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	Up to 30 ppm Colour and Black and White Up to 24 ppm Colour and Black and White Up to 28 ppm Colour and Black and White			
Two-Sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	NAUp to 18 ppm Colour and Black and WhiteNAUp to 17 ppm Colour and Black and WhiteNAUp to 19 ppm Colour and Black and White			
Monthly Duty Cycle ¹	Up to 50,000 pages / month			
Recommended Average Monthly Print Volume ²	Up to 3,000 pages	Up to 3,000 pages		
Processor	1.05 GHz			
Memory	2 GB			
Connectivity	10/100/1000Base-T Ethernet USB 3.0		10/100/1000Base-T Ethernet USB 3.0 Wi-Fi 802.11n Wi-Fi Direct [®]	
Paper Handling	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
Document Feeder				
Capacity ³	Single-pass Duplex Automatic Document Feeder (DADF): 50 sheets			
Sizes	Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm			
Weights	16 lb. bond to 45 lb. cover / 60 to 125 gsm			
Bypass Tray				
Capacity ³	50 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm			
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled			
Τταγ 1				
Capacity ³	250 sheets			
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm			
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm			

Τταγ 1			
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Optional Tray 2			
Capacity ³	550 sheets		
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 1	91 mm to 216 x 356 mm	
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Total Capacity			
Device Standard Capacity ³	300 sheets		
Device Total Capacity ³	850 sheets		
Paper Output			
Output Capacity ³	150 sheets		
Automatic 2-Sided	NA	Standard	
Device Specification	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI
Electrical Requirements			
North America	Voltage: 120 VAC +/- 10% Frequency: 60 Hz +/- 3 Hz, 12A		
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50 Hz +/- 3 Hz, 6A		
Power Consumption			
Operation ⁴	120V: Maximum 350 watts 220V: Maximum 370 watts		
Standby Mode [®]	120V: Maximum 51 watts 220V: Maximum 52 watts		
Power Off Mode	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts		
Sleep Mode ⁴	120V: Maximum 1.1 watts 220V: Maximum 1.2 watts		
Warm-up (from Sleep Mode)	As fast as 27 seconds		
Operating Environment			
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C		
Required Reletive Humidity	15% to 85%		
Sound Power Levels Operating Standby	6.84 B or less 4.25 B or less		
Sound Pressure Levels Operating	52.5 dB(A) or less		

Operating Environment	26.2 dP(A) or loss			
Standby	26.3 dB(A) or less			
Dimensions and Weight (unpackaged)				
Workcentre 6515N, DN, and DNI	Width: 16.5 in. / 420 mm Depth: 19.9 in. / 506 mm Height: 19.7 in. / 500 mm Weight: 67.7 lb. / 30.7 kg			
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg			
Dimensions and Weight (packaged)				
Workcentre 6515N, DN, and DNI	Width: 25 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 26 in. / 659 mm Weight: 79.8 lb. / 36.2 kg			
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg			
System Certification/Regulatory Complian	ce			
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition NOM GS Mark EAC Citrix [™] Certified Cerner (undergoing evaluation) Apple® AirPrint® certification Google Cloud Print [®] Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Сору	WorkCentre 6515N WorkCentre 6515DN	WorkCentre 6515DNI		
Document Scanner	Single-pass Duplex Automatic Document Feeder (DADF) with 50-sheet capacity			
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 DADF: 8.5 x 14 in. / 216 x 356 mm			
Simplex Speed	Black and White: Up to 25 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Colour: Up to 12 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm			
Duplex Speed	Black and White: Up to 37 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Colour: Up to 21 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm			
First-Copy-Out Time	As fast as 12 seconds from the Platen			
Sides (input:output)	1:1, 1:2, 2:2, and 2:1			
Quantity	1 to 999			
Resolution	Up to 600 x 600 dpi			
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments			
Concurrency	Concurrent scanning and printing			

Сору	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI
Copy Features	Automatic Background Suppression Book Copying Book Copying with Centre Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce/Enlarge (25%-400%) Image Shift Original Type Sample Copy Sharpness		
Print	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI
First-Page-Out Time	As fast as 12 seconds Colour and Blo	ack and White	
Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	Adobe [®] PostScript [®] 3 [™] PCL [®] 5e, 6 PDF TIFF		
Maximum Print Area	4 mm from all edges		
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-or Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks	colour Simulations	
Print from USB	Allows walk-up printing from Type A Supports direct printing from compu Supported file formats: PDF, JPEG, T	uter via Type B USB port	
Operating Systems	Windows [®] , 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 Mac OS [®] version 10.5 and higher Citrix [®] Redhat [®] Enterprise Linux [®] IBM [®] AIX [®] 5 HP-UX [®] 11iv2 Oracle [®] Solaris 9, 10 Fedora Core 12-15 SUSE [®]		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, I SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour [®] / Airprint [®] FTP Most protocols not in use can be dis	Raw Socket Printing/Port 9100, IPv4/IPv6, WSI sabled	D
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP Aut	tonet, TLS, SNTP, MDNS	
Font Capability	136 PostScript fonts 88 PCL fonts		
Mobile Solutions and Mobile Device Apps			
Xerox [®] Mobile Express Driver [®]	Mobile Express Driver automatically	discovers available printers and provides state	vices in every new location. Plug into a new network, and us and capability information. Save a list of "favourite" any network, and greatly reduce mobile support calls to
Xerox [®] Global Print Driver [®]			ge Xerox® and non Xerox® devices from a single driver. It support calls, and simplifying print services management.

Google Cloud Print [™] Go Kerox [®] Print Service Plug-in for Android [™] Th (Free at Google Play [™] Store) Th Xerox [®] Mobile Link App (Free at Google Play [™] Th Store and Apple [®] App Store) Th	Vith AirPrint, an iPhone or iPad auto ioogle Cloud Print connects print do hromebook [™] notebook computers he Xerox [®] Print Service Plug-in for A rint drivers.You can easily print pho vireless network. A robust print opti ne Google Play [™] store. he Xerox [®] Mobile Link App allows y	promatically locates and connects to the AirPrini evices to the web, enabling users to print the c and any other web-connected device. Android KitKat (4.4 or greater) devices streaml itos, Web pages and documents when your m		
Kerox® Print Service Plug-in for Android™ The form of the prime of the prim	hromebook [™] notebook computers he Xerox [®] Print Service Plug-in for A rint drivers.You can easily print pho vireless network. A robust print opti he Google Play [™] store. he Xerox [®] Mobile Link App allows y	and any other web-connected device. Indroid KitKat (4.4 or greater) devices streaml itos, Web pages and documents when your m	nes mobile printing without third-party apps or additional	
 (Free at Google Play[™] Store) privit the set of t	rint drivers.You can easily print pho irieless network. A robust print opti ne Google Play [™] store. he Xerox [®] Mobile Link App allows y	tos, Web pages and documents when your m		
Store and Apple® App Store) se fui mi		The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.		
Xerox [®] Wireless Print Solutions Adapter (Op- Th	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer. (Available early 2017)			
	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA			
Scan W	VorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
Capability Ca	olour and Black-and-white			
Concurrency Sc	can while the system is printing co	py or network print jobs, or while it is transferri	ng scan to network or fax jobs	
Input Speed - Black and White Sc	can up to 37 ipm – 8.5 x 11 in. / A4	ı / 210 x 297 mm		
· · ·	can up to 21 ipm – 8.5 x 11 in. / A4			
· · ·	ptical – 600 x 600 dpi			
	24-bit Colour / 8-bit Greyscale			
	Platen: Up to 8.5 x 11.7 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm			
SN	FTP SMTP SMB/SMB2			
Sir PD	JPG Single-page and Multi-page TIFF PDF Searchable PDF with integrated OCR			
	WIA TWAIN			
Sc Sc Sc Sc Sc Sc Sc Sc Sc Sc Sc Sc Sc	can to Email (local address book or can to Network (via FTP/SMB) can to USB Memory Device can to Email (SMTP) can to WSD can to Application (TWAIN Networ can to MIA (WSD Scan) can to Mac 10.9 or later (Network/ can to Network Computer (SMB/FT) can to Multiple Destinations in a Si	rk) Mac ICA) 'P)		
Security W	VorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
IP: 8C S/I IP Se Se SN LD Ne	ecure HTTPS (TLS) Psec 02.1x Authentication /MIME P Filtering ecure Print ecure Fax Receive NMP v3 DAP (SASL) letwork Authentication erberos Authentication (Unix / Linu	ux / Windows ADS)		
Fax ⁵ W	VorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
Fax Speed 33	3.6 Kbps			
Memory 41	MB			
Resolution Up	Jp to 400 x 400 dpi			
	/H/MR/MMR/JBIG			

Fax⁵	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
Fax Features	Broadcast Sending (up to 200 destinations) Delayed Start (up to 24 hours) Distinctive Ring Pattern Detection Fax Address Book (up to 200 speed dials) Fax Forward to Email Fax Forwarding and Local Print Polling Receive Reject Junk Fax Secure Fax Receive			
Device Management				
Xerox [®] CentreWare [®] Web				
	whether running Windows or UNIX or anyWorks with any SNMP-managed printer from the state of the state of	other operating system	ts web browser-based device management from any workstation, d troubleshooting, and device upgrades, as well as basic accounting	
Xerox® Embedded Web Server - Integrate	d Device Web Page			
Device Status	Web server embedded • Tray status/contents • Consumables status	Tray status/contents		
Print Queue Viewing	Complete job print queue management—he	old, release, promote and de	lete	
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG) Output feature selection			
Device Administration	Allows simple, remote installation setting of	configuration options and r	nanagement of the device.	
Browsers	Microsoft [®] Internet Explorer 11 Microsoft Edge [™] 38 Mozilla [™] Firefox [®] 48 Apple [®] Safari [®] 9.1 Google Chrome [™] 52 Opera [™] 39			
Remote Print Services				
Xerox [®] MeterAssistant [®] Service		Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time- consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] SuppliesAssistant [®] Service	Automatically orders supplies for Xerox® outp	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.			
What's In The Box				
	 WorkCentre 6515 Colour Multifunction Printer Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁶; Black: 1,500 print capacity⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord 			
Supplies and Accessories	Quantity	P	art Number	
Supplies				
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages ⁶ Magenta: 4,300 standard pages ⁶ Yellow: 4,300 standard pages ⁶	1	OGRO3693 OGRO3694 OGRO3695	
High Capacity Print Cartridges	Black: 5,500 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶	1	06R03488 06R03485 06R03486 06R03487	
Standard Capacity Print Cartridges	Black: 2,500 standard pages ⁶ Cyan: 1,000 standard pages ⁶ Magenta: 1,000 standard pages ⁶ Yellow: 1,000 standard pages ⁶	1	06R03484 06R03481 06R03482 06R03483	
Drum Cartridge	Black: 48,000 pages ⁷ Cyan: 48,000 pages ⁷ Magenta: 48,000 pages ⁷ Yellow: 48,000 pages ⁷	1	08R01420 08R01417 08R01418 08R01419	
Waste Cartridge	30,000 pages	1	08R01416	

Accessories		
550-sheet Paper Tray	097S04765	
Wireless Network Adapter	497K16750	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ² Expected regular monthly throughput.
 ³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 ⁶ Power states defined per ENERGY STAR[®] Programme requirements for Imaging Equipment.
 ⁵ Requires analogue phone line.
 ⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print
 ⁷ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.



For more information, visit us at www.xerox.com/office

©2016 Xerox Corporation. All rights reserved. Xerox[®], Xerox and Design[®], CentreWare[®], Global Print Driver[®], MeterAssistant[®], Mobile Express Driver[®], SuppliesAssistant[®], and WorkCentre[®] are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR[®] partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency (DN and DNI configurations). ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 11/16 BR19949 65XSS-021A